



CONSTANT PRESSURE, PUMP & PRESSURE TANK SYSTEMS (MODEL RRS)

ELEVATING THE STANDARD.

100 E. Kelso Road Kaukauna, WI 54130
phone: 920-423-7170 fax: 844-348-9001
info@velocitywaterworks.com www.velocitywaterworks.com



RRS-40

SUBMERSIBLE PUMP RRS SYSTEM

This system boasts a small footprint with 20 gpm flow (27 gpm max). 120V Submersible Stainless Steel Pump that includes a 20 ft power cord. (230V 1-Phase Option is available.) Stainless steel wall mount bracket houses the control box and 5ga in-line pressure.

Outlet assembly includes stainless steel fittings, pressure switch, pressure gauge, stainless steel check valve and barbed fittings for quick connection of inlet and outlet.

System also includes low limit safety shut-off assembly and optional low limit tank fill system.

SIZES AVAILABLE

20, 40, 60 and 80 gpm systems. Customizable systems available.

APPLICATIONS

Reject Recovery Systems save operator money by capturing & re-using RO Reject Water. RO/Spot-free Delivery Constant Pressure Systems for higher volume applications.

PUMP & PRESSURE TANK

Stainless Steel pumps with (TEFC) motors and pressure tanks sized to prevent 'quick cycling.' Pumps are standard 230V. 3-Phase & 110V available.

SAFETY

Low Limit Safety (LLS) Shut-Off to prevent pump from operation if a low level situation occurs within the holding tank.

OPTIONS

- (LLF) Low Limit Tank Full Assembly
- (FWB) Fresh Water By-Pass Assembly
- 3-Phase & 110V systems available
- Holding Tanks ordered separately

