



VELOCITY WATER WORKS REVERSE OSMOSIS SYSTEMS SPECIFICATIONS (VROF / VROW)

ELEVATING THE STANDARD.

100 E. Kelso Road Kaukauna, WI 54130

phone: 920-423-7170 fax: 844-348-9001

info@velocitywaterworks.com www.velocitywaterworks.com



VROW-2



VROF-4



VROF-8



VROF-12

	Model #	¹ Production (GPD)	Membranes (Qty)	² Recovery Rate (%)	Product Flow (GPM)	Reject Flow (GPM)	Pump Size (hp)	Inlet (FPT ³)	Product Outlet (MPT ⁴)	Reject Outlet (MPT ⁴)	Dimensions (W"xD"xH")	Shipping Weight (lbs.) RO System / Carbon Filter
Free Standing	VROF-18	1,800	1	60%	1.2	0.80	1/2	3/4"	1/2"	1/2"	³ 26"x30"x68"	168 / 72
	VROF-1	2,400	1	60%	1.7	1.20	1.0	3/4"	1/2"	1/2"	³ 26"x30"x68"	170 / 72
	VROF-2	4,800	2	70%	3.4	1.5	1.0	3/4"	1/2"	1/2"	³ 26"x30"x68"	182 / 96
	VROF-3	7,200	3	70%	5.0	2.2	2.0	3/4"	1.0"	1/2"	³ 28"x30"x68"	225 / 130
	VROF-4	9,600	4	70%	6.7	2.9	2.0	1.0"	1.0"	1/2"	³ 29"x30"x68"	244 / 158
	VROF-5	12,000	5	70%	8.3	3.6	3.0	1.0"	1.0"	1.0"	⁴ 26"x30"x68"	268 / 319
	VROF-6	14,400	6	70%	10	4.3	3.0	1.0"	1.0"	1.0"	⁴ 26"x30"x68"	289 / 352
	VROF-8	18,000	8	70%	12.5	5.4	3.0	1.0"	1.0"	1.0"	⁴ 26"x30"x68"	308 / 352
	VROF-12	28,000	12	70%	19.4	8.4	5.0	1.50"	1.0"	1.0"	⁴ 26"x30"x68"	Call
Wall Mount	VROW-18	1,800	1	60%	1.2	0.80	1/2	3/4"	1/2"	1/2"	22"x14"x48"	148 / 72
	VROW-1	2,400	1	60%	1.7	1.20	1.0	3/4"	1/2"	1/2"	22"x14"x48"	154 / 72
	VROW-2	4,800	2	70%	3.4	1.5	1.0	3/4"	1/2"	1/2"	22"x14"x48"	165 / 96

¹ Production Rates are based upon adequate water supply of Chlorine free, 77° F Soften Water.

² Recovery Rate %'s fluctuate based upon feed water quality. Rejection Rates listed are minimum settings.

³ Carbon Filter comes mounted to RO Frame and pre-plumbed to RO System.

⁴ Carbon Filter comes as a stand alone system (option is available to have Carbon Filter mounted to RO Frame)