



FREE STANDING (VROF) REVERSE OSMOSIS SYSTEMS

ELEVATING THE STANDARD.

100 E. Kelso Road, Kaukauna, WI 54130
phone: 920-423-7170 fax: 844-348-9001
info@velocitywaterworks.com www.velocitywaterworks.com



VROF-6 (14,400 GPD)



VROF-9 (18,000 GPD)



VROF-12-3-D (28,800 GPD)

MODEL VROF

Free standing standard models are available in 2400gpd (2 membrane) up to 28,000gpd (12 membrane). Custom sizing is also available.

VROC RO CONTROLLER

Panel mounted with Digital TDS Display. State of the art technology gives piece of mind to operator.

FRAME

Stainless steel welded to a minimal footprint, yet maximizing the accessibility of the system.

MEMBRANES AND HOUSINGS

Stainless steel housings are home for our high performance membranes handling high flow rates and also an excellent salt rejection rate.

METERS AND GAUGES

Two (2) flow meters and three (3) pressure gauges panel mounted for easy visibility and accessibility.

SAFETY AND FUNCTION

Product float switch, auto membrane flush, low pressure safety shutoff and continuous system performance updates keep the operator informed.

AUTOMATIC RESTART

In cases of power failure or pressure fault, the VROF system will automatically turn back on to ensure continuous production.

SEDIMENT FILTER

Accessibility friendly to the operator, the 5-micron sediment filter will help to keep your system functioning at its most efficient level. One additional filter included.

CARBON FILTER

Every system includes an auto backwashing carbon filter. The filter comes standard mounted to the system on our 9600 (4 membrane) and smaller. Optional mounting for larger systems can be custom ordered.